No. 1739 16-2-28

Hobbies FRETWORK DESIGN

The ⟶ indicates direction of grain of wood.

CLOCK

For Prices of Wood and Fittings see current Catalogue, or on application.

TOP A OF CLOCK. Cut one 3/16 in. thick.

SECTION SECTION Section

TOP B OF CLOCK. Cut one 3/16 in. thick & shape to section.

— SIZE —
HEIGHT 9⅞ in.
WIDTH 8¾ in.
DEPTH 3½ in.

WOOD REQUIRED—1 PANEL A AND 1 PANEL B.

SIDE BACK SIDE

FRONT

TOP OF CLOCK. Cut one 3/16 in. thick and shape to section.

BACK OF BASE

CENTRE LINE

NOTE.—The Hobbies Presentation Designs are not given away with back numbers of Hobbies. Additional copies may be had from Hobbies Ltd.

SIDE OF BASE

BOTTOM OF BASE. Half only shown. Cut one 3/16 in. thick.

FRONT OF BASE

BEADING No. 58

FEET. Cut four 3/16 in. thick.

BASE

BRASS RIM OF CLOCK

BEADING No. 53

Front of Clock. Cut one ¼ in. thick. Dotted lines indicate positions of overlays and beadings.

BEADING No. 53

SIDE BRACKETS SIDE BRACKETS

Cut one of each ½ in thick.

HALF-ROUND BEADING No. 53. 1 FOOT REQUIRED.

QUARTER-ROUND BEADING No. 58. 2 FEET REQUIRED.

TOP B TOP A TOP OF CLOCK SIDE

DETAIL OF TOP OF CLOCK

OVERLAYS. Cut one of each 3/16 in. thick.

SCREW

SIDES OF CLOCK. Cut two ¼ in. thick.

SIDE BRACKET SCREW INTO FRONT

BACK

SCREW INTO BACK SIDE BRACKET

BACK PLATE OF CLOCK

Back of Clock. Cut one ¼ in. thick

ADDRESSES.

All orders by post should be addressed—HOBBIES LIMITED, Dereham, Norfolk. Customers residing in the neighbourhood may obtain Tools, Wood and Fittings by calling at the HOBBIES Supply Stores.

LONDON : 65 New Oxford Street, W.C.
" 147 Bishopsgate, E.C.
" 79 Walworth Rd., S.E.
GLASGOW : 326 Argyle Street.
MANCHESTER : 10a Piccadilly.
BIRMINGHAM : 9a High Street.
LEEDS : 10 Queen Victoria Street.
Briggate.
SOUTHAMPTON : 25 Bernard St.
BRIGHTON : 68 London Road.
SHEFFIELD : 214 West Street.
TORONTO : 385½ Yonge Street.
And at all HOBBIES Authorised Agents.

PRINTED IN ENGLAND

www.finescrollsaw.com

SIDE BRACKET SIDE BRACKET

BACK

SIDE SIDE

TOP OF BASE. Cut one 3/16 in. thick.

SIDE BRACKET SIDE BRACKET

OVERLAY

SIDES OF BASE. Cut one of each 3/16 in. thick.

BACK OF BASE. Cut one ¼ in. thick.

NOTE—The fretted front and sides of base should have a backing of either Jap veneer or 1/16 in. wood.

QUARTER ROUND BEADING

FRONT OF BASE. Cut one ¼ in. thick.

QUARTER ROUND BEADING No. 58